

Artikelnummer: 83222201

Bedrukking mogelijk



Industrial / ISO pallet CS3-L - 1200 x 1000 mm - with 7 mm rims - 3 pallet skids, open with reinforcement ribs - black ESD



Product specificaties

External dimensions (L x W x H)	1200 × 1000 × 150 mm
Dynamic load capacity	1000 kg
Material	HDPE with carbon compound
Article number	83222201
Weight (kg)	15,2 kg
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	Black
Surface resistance	?1x10 E4 Ohm to <1x10 E11 Ohm
Static load capacity	5000 kg
Edge height	7 mm
Load capacity in racks	400
Quantity per pallet	16

Eigenschappen

Electrostatic dissipative (ESD): protects sensitive components against charge build-up and electrostatic discharge

Undersides of blocks and pallet skids are open with reinforcement ribs

Raised rims around the deck of the CS3-L prevent loads from slipping and prevent empty pallets from sliding on each other

The CS3-L is extra strong thanks to the robust connection between the skids and the blocks

Optional fully welded (closed) skids increase the pallet's strength and impact resistance

Marking, logos or numbering on request; location to be agreed

Options: Pallet lid / pallet cover - QR codes and barcodes - RFID transponders - closed skids - version without rims, with 7 or 22 mm deck rims, with 22 mm side rims along the deck

Omschrijving

Our ESD pallets are produced from high-quality plastic to which an ESD compound is added. This gives the pallet electrically conductive properties. It prevents electrostatic build-up and subsequent discharge, which can damage sensitive electronics. The CS3-L is designed for efficient transport of Euro standard stacking bins (ESD version). For additional centring of a full pallet load with stacking bins, we supply a 1200 x 1000 mm pallet lid in an ESD version.



Alternatieve artikelen



83192201



83182222



83102222