



Industrial pallet H3-L - 1200 x 1000 mm - with 7 mm rims - 3 open pallet skids - black ESD



Product specificaties

External dimensions (L x W x H)	1200 × 1000 × 160 mm
Dynamic load capacity	1250 kg
Material	HDPE with carbon compound
Article number	83182222
Weight (kg)	21,5 kg
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	Black
Surface resistance	?1x40 E4 Ohm to <1x10E11 Ohm
Static load capacity	5000 kg
Edge height	7 mm
Load capacity in racks	850
Quantity per pallet	15

Eigenschappen

Electrostatic dissipative (ESD): protects sensitive components against charge build-up and electrostatic discharge

Undersides of blocks and pallet skids are open (ribbed)

Raised rims around the deck of the H3-L prevent loads from slipping and prevent empty pallets from sliding on each other

The H3-L is extra strong thanks to the robust connection between the skids and the blocks

Marking, logos or numbering on request; location to be agreed

Options: Pallet lid / pallet cover - QR codes and barcodes - RFID transponders

Omschrijving

Our ESD pallets are produced from high-quality plastic to which an ESD compound is added. This gives the pallet electrically conductive properties. It prevents electrostatic build-up and subsequent discharge, which can damage sensitive electronics. The H3-L pallet is designed for efficient transport of Euro standard stacking bins (ESD version). For additional centring of a full pallet load with stacking bins, we supply a 1200 x 1000 mm pallet lid in an ESD version.



Geschikte accessoires



Alternatieve artikelen

