

Artikelnummer: 55.1212MB3RR

Bedrukking mogelijk



Export pallet / drum pallet 1212MB3RR

- 1200 x 1200 mm - on 3 runners - with 5 mm raised rim all around - standard regrind - black



Product specificaties

External dimensions (L x W x H)	1200 × 1200 × 156 mm
Dynamic load capacity	1375 kg
Material	Standard regenerate
Article number	55.1212MB3RR
Weight (kg)	16,1 kg
Temperature range	-20°C to +40°C / briefly up to +90°C
Color	Black
Static load capacity	4000 kg
Edge height	5 mm
Load capacity in racks	250
Quantity per pallet	15

Eigenschappen

Plastic pallet type 1212MB3RR in light/medium version (1200 x 1200 mm) for transport and storage of steel drums (e.g. 4 units of 200 liter)

Equipped with 3 pallet runners

With open pallet deck

With 5 mm raised rims around the pallet deck

Load capacity: static 4000 kg - dynamic 1200 kg - in pallet racking 200 kg

Produced from standard regrind material

Does not absorb moisture and does not develop mould

For trouble-free export to IPPC countries in accordance with ISPM 15

No treatment against unwanted insects and other pests is required

Options: version on 6 runners - version with closed deck

Omschrijving

Plastic pallet type 1212MB3RR (1200 x 1200 x H 156 mm) is mainly used as a drum pallet - for transport and storage of 200 liter steel drums. Four drums of this type fit on this pallet.

The pallet has an open deck with 5 mm raised rims all around. It is also fitted with 3 pallet runners. Produced from standard regrind material.

Alternatieve artikelen

