

Artikelnummer: KER10050182



Plastic rack / Euro shelving unit - 1000 x 500 x H 1820 mm - 4 shelves - spacing 500 mm - green / grey



Product specifications

External dimensions (L x W x H)	1000 × 500 × 1820 mm
Material	PVC
Article number	KER10050182
Weight (kg)	24,5 kg
Temperature range	-40°C to +40°C / briefly up to +80°C
Color	Green
European Article Number	7424926516521
Number of shelves	4
Shelf spacing (mm)	500
Underneath space (mm)	120
Upright spacing (mm)	850

Eigenschaften

Plastic rack as a Euro shelving unit in standard format. Dimensions 1000 x 500 x H 1820 mm - colour green, with grey accents (DESIGN version)

Fitted with 4 shelves - depth 500 mm

Space between the shelves: 3 x 500 mm - free clearance underneath 120 mm

Divided by 2 uprights - spacing 850 mm

Load capacity: 200 kg per linear metre of shelf, per level (with 4 shelves this means 4 x 200 kg per metre of shelving)

Storage system for various storage needs - robust - lightweight

Easy to assemble - without tools

Easy to clean - corrosion-free - HACCP-compliant

Food-safe and highly chemical-resistant (e.g. chlorine)

Options: green with red accents (CLASSIC version) - grey with grey accents (GREY version) - mobile - different clearance underneath - custom-made

Accessories: cover plates for shelves - label holders - adjustable feet

Omschrijving

Plastic rack designed as a Euro shelving unit in **standard format**. Particularly robust stacking rack made entirely from green plastic with accents in stylish grey (DESIGN version).

Dimensions

The external dimensions are 1000 x 500 x H 1820 mm. The total length of 1000 mm is divided by 2 uprights with a spacing of **850 mm**. The shelving unit is fitted with 4 shelves of **500 mm** depth - the space between the shelves is **3 x 500 mm** - the bottom shelf has a free clearance underneath of **120 mm**.

Performance

The free clearance underneath makes it easy to clean **under** the shelf. The shelves themselves are easy to clean with water and soap.

The **load capacity** of Euro shelving units is approx. 200 kg per linear metre of shelf, per level (with 4 shelves this means 4 x 200 kg per metre of shelving). The load must be evenly distributed; heavy products should be placed near the uprights.

In addition, Euro shelving units are particularly **impact- and shock-resistant**, **corrosion-free** and very **easy to clean**.

Euro shelving units are suitable for **direct** contact with unpackaged food. PVC is used as the raw material for the shelving units because rigid PVC is highly **chemical-resistant** and, for example, offers excellent resistance to salts and chlorine.

