

Artikelnummer: 52.RC682F.IWBV.2

Bedrukking mogelijk



# Roll container - for Euronorm - 2 clamp frames, galvanised - plastic base, grey



## Product specificaties

|                                  |                                                          |
|----------------------------------|----------------------------------------------------------|
| External dimensions ( L x W x H) | 815 × 682 × 1710 mm                                      |
| Internal dimensions (L x W x H)  | 815 × 615 × 1500 mm                                      |
| Dynamic load capacity            | 500 kg                                                   |
| Article number                   | 52.RC682F.IWBV.2                                         |
| Weight (kg)                      | 24 kg                                                    |
| Color                            | Grey                                                     |
| Bottom                           | Perforated - reinforced                                  |
| Type                             | For Euronorm bins, crates, boxes etc.                    |
| Design                           | Demountable                                              |
| Base material                    | HDPE - plastic                                           |
| Structure                        | 2-sided / clamp frames                                   |
| Wall material                    | Steel - hot-dip galvanised                               |
| Wheels                           | 2 fixed and 2 swivel castors Ø 125 mm                    |
| Fork material                    | Steel - electrolytically galvanised                      |
| Wheel construction               | Nylon rim - rubber tread (non-marking - noise-dampening) |
| Extra                            | Plastic tension straps (2)                               |

## Eigenschappen

**Roll container (815 x 682 x H 1710 mm) for Euronorm bins, crates and packaging**

**With an internal platform size of 815 x 615 mm - e.g. for 2 bins 600 x 400 mm side by side**

**2-sided version - usable internal height: 1500 mm**

**Base platform made of food-safe grey plastic**

**Equipped with 2 fixed and 2 swivel castors Ø 125 mm**

**Fitted with electrolytically galvanised wheel forks**

**Wheel construction: nylon rim - rubber tread (non-marking - noise-dampening - shock-absorbing)**

**The container is fitted with hot-dip galvanised insert walls**

**The walls are inserted into the container base**

**The hook-shaped insertion pins clamp the add-on walls securely into the container base**

**Locking is done by the oval drop rings**

**The add-on walls can also be removed again without tools**

**The 2-sided roll container is supplied with 2 plastic tension straps**

**Options: lettering - QR codes and barcodes - layer pads - coversheet - braked wheels - other wheel construction (e.g. hard nylon) - stainless steel - other wheel diameter - other container structure - folding couplings (for towing units)**

## Omschrijving


Grey 2-sided roll container (815 x 682 x H 1710 mm) with a usable platform size of 815 x 615 mm, suitable for Euronorm bins, crates and boxes. For example, two Euronorm bins 600 x 400 mm can fit side by side on the roll container. The roll container is fitted with a grey base platform made of food-safe plastic, equipped with smooth-running fixed and swivel castors Ø 125 mm. The forks of both the fixed and swivel castors are electrolytically galvanised. The wheels are constructed with a nylon rim fitted with a non-marking rubber tread. The version with rubber tread is particularly low-noise.

The structure of the roll container is designed with two steel clamp frames in a hot-dip galvanised finish. The side walls are inserted into the base platform and clamp themselves in place because the ends are slightly bent, creating a hook-shaped insertion pin. As a result, the add-on wall clamps itself into the base. The add-on wall is locked by the oval drop ring located in the centre of the add-on wall. When this is pushed upwards, the add-on wall can be removed from the base again. Because the clamp frames are hot-dip galvanised, they are suitable for long-term outdoor use.

The version with 2 frames is particularly practical as it can be loaded from both sides; unloading at the destination can also be done flexibly from two sides. In addition, protruding loads can be distributed to some extent. For this reason, this 2-sided version is the most commonly used design for long-term outdoor use.



## Geschikte accessoires



## Alternatieve artikelen

